

3400SE

Laundered, 100% continuous filament polyester fiber, heavy weight. Edges are ultrasonic cut and sealed.

Property	Typical Value	Test Method
Basis Weight		
(oz/yd ²)	4.3	
(g/m ²)	146	
Thickness		
(mils)	22	
(mm)	0.56	
Sorbency Capacity		
Intrinsic (mL/g)	2.9	IEST-RP-CC004.3
Extrinsic (mL/m ²)	400	IEST-RP-CC004.3
Nonvolatile Residue (NVR) (g/m²)		
Deionized Water	0.019	IEST-RP-CC004.3
Isopropyl Alcohol	0.019	IEST-RP-CC004.3
Ions (ppm)		
Sodium	1.1	IEST-RP-CC004.3
Chloride	1.3	IEST-RP-CC004.3
Particles (million/m²)		
0.5 - 5.0 µm	6.7	IEST-RP-CC004.3
5.0 µm and Larger	0.09	IEST-RP-CC004.3
Fibers (fibers/m²)		
>100 µm	272	IEST-RP-CC004.3

Notes:

- 1) Data shown are typical values at the time of publication and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions. Current and/or comparison data may be available. Please contact an FG Clean Wipes representative for details.
- 3) FG Clean Wipes makes general recommendations on which wipers are suitable for different cleanroom classifications. However, specific applications may affect that recommendation. The final decision should be made by the end user for their particular application.